



LEGEND

- ▬ Traffic Sign
- ▬ Sequencing Arrow (Type "C")
- ▬ Truck Mounted Attenuator (TMA)
- ※ Amber revolving light or amber strobe light

1. This layout is intended to show traffic control requirements for milling and fog-sealing shoulder rumble strips.
 2. Vehicles with amber flashing lights should be visible to the vehicle with amber flashing lights ahead and behind them.
 3. For fog seal operation, place a 1200 mm x 1200 mm FRESH OIL sign (W21-2) at the beginning of the work area. Place additional FRESH OIL signs at the end of each ramp (or Intersection) and periodically through the work area so that signs are no more than 3200 meters apart.
 4. For milling operation, Work Vehicle #1 is debris removal equipment and Work Vehicle #2 is milling machine.
- For fog seal operation, Work Vehicle #1 is fog seal truck and Work Vehicle #2 is not used.

All dimensions given in millimeters unless noted.

M METRIC VERSION	 Iowa Department of Transportation Highway Division		
	STANDARD ROAD PLAN		RS-41
	REVISION: NEW.		REVISION NO. NEW
	 APPROVED BY DESIGN METHODS ENGINEER		REVISION DATE 10-18-05
			MILLED SHOULDER RUMBLE STRIPS (MULTI-LANE ROADWAY)